

IOXIDE

WATER SANITATION



NO SILVER SALT



NO HEAVY METAL



- Based on stabilised hydrogen peroxide



- Removes organic contaminations and manganese deposit



- For powerful and effective treatment of all watering and drinking systems



- Safe for humans, animals and materials



Effective clean and disinfect drinking Systems

Clean drinking systems regularly. In our daily lives we hardly pause for a moment to consider that water is one of the primary essentials of life for human and animals. Rather strange actually! Certainly if we are aware of what can go wrong with the quality of drinking water, for example, through contamination of the drinking water system. Ioxide cleans the complete drinking water system (storage reservoirs, pipes, drinking nipples, cups and drinking bells) in a simple manner, both during and after the production period.



Cleaning empty buildings. Preferably clean the entire drinking systems when the buildings are empty. For the purpose, a 1 – 3 % Ioxide solution is recommended (1% - 1 liter Ioxide per 100 liters of water). The effervescent action makes brushing unnecessary. There must be sufficient aeration on the drinking system. After the pipes have been filled completely, the drinking nipples, cups and bells can be filled. The applied solution does not have to be circulated through the system. After the product has had time to soak in for at least 10 hours, the entire system can be rinsed with clear water.



Cleaning full operational systems. Drinking systems can also be cleaned while operational. In this case, always start the process with a 0.005% dosage (= 50 ml Ioxide per 1.000 liters of water). Subsequently, the dosage is increased by 50 ml every second day until the maximum dosage of 0.025% (= 250 ml Ioxide per 1.000 liters of water) is reached. Depending on the extent and type of contamination, this cleaning method takes about 10 days.



Preventive treatments. In practice (medicines and feed supplements) can cause considerable scaling in drinking water systems. Using Ioxide, this can be easily be prevented. For example, deposit forming in pipes can be prevented by adding 50 – 100 ml Proxide per 1.000 liters of drinking water for one day, immediately after using an additive.

Ioxide can be delivered in:

- ✓ 1 liter packed in a box
- ✓ Can: 5 liters
- ✓ Can : 10 liters

